

TG42/15 IP23

PTO SHAFT GENERATORS



Image purely indicative

The TG class generator can produce high quality power for any agricultural use.

Power

Three phase power COP	kVA	42.0
Single phase power COP	kVA	14.7

Specifications

Voltage	V	400/230
Frequency	Hz	50
Power factor	cos ϕ	0.8/1
Gear box revolution	rpm	1500
Power (tractor)	kW/HP	74/100
Revolution PTO shaft	rpm	395
Voltage regulation system		Electronic AVR
Voltage Accuracy	%	0.5



Dimensional data

Length	(L) mm	1110
Width	(W) mm	720
Height	(H) mm	1322
Dry weight	Kg	355

Equipments

Thermomagnetic protection	X
Differential protection	X
Voltmeter	X
Frequency meter	X

Sockets

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 32A IP44	1
3P+N+T CEE 400V 63A	1

Alternator & Socket protection

Electric protection	IP23
Panel protection	IP44



The information is aligned with the Data file at the time of download. Printed on 15/01/2021 (ID 2336)

©2021 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

