BSI 50/218




FEATURES:

- Preconfigured battery storage kit for indoor use
- Battery inverter and energy management system (EMS) perfectly harmonised by in-house development
- Modular battery and combiner racks for simple capacity and power expansion
- Comprehensive EMS with peak shaving, self-consumption optimisation, time-of-use and much more integrated into the system at the factory
- Maximum security with state-of-the-art software architecture (GDPR-compliant)
- High accessibility for user-friendly maintenance (max. once a year)
- 10-year performance warranty with a wide temperature range

General technical data		
Rated apparent power	kVA	50
Rated voltage	Vac	400
Frequency	Hz	50
Maximum AC current	A	73
Battery cell	Type	Li-Ion (LFP) Pouch
Total capacity	kWh	218
Rated net capacity (90%DoD)	kWh	196



Inverter		
Quantity	n.	1
Rated apparent power	kVA	50
Maximum AC current	A	73
Power factor / Range		1 / 0i ... 0c
Initial short circuit current (Ik“)	A	73



Battery		
Quantity of module	n.	46
Module capacity	kWh	4.74
Rated Voltage	V	736
Max. C-rate		1C
Battery cell	Type	Li-Ion (LFP) Pouch
Cycles @ 90% DoD | 65% SoH	n.	7300




www.pramac.com

Technical data - Energy Management System		
Voltage supply	VDC	24
RJ45 dedicated MAC adresses for OT/IT use	n.	2
Encrypted MQTTS communication		√
Digital cloud twin		√
2-factor authentication		√
Communication Interface Ethernet (Modbus TCP/IP / local and cloud-to-cloud REST API)		√
• **Possible Applications**		:
Self-consumption optimization (SCO)		√
Peak shaving (PS)		√
Time-based charging/discharging (ToU)		√
Combined operation (multi-use e.g. PS and SCO)		√
Energy trading		√
Simple management of charging stations		√
Load management and prioritisation for charging points		√
Integration of Plant controllers		√



Installation data		
AC-Grid connection ON-Grid		3P, PE / TT, TN-C, TN-S
AC-Aux. grid connection ON-Grid		1P, N, PE / TN-C-S
Communication Interfaces RJ45 (Ethernet)		√
[1] Battery Rack	(L/W/H) mm	815x696x2130
CombinerRack	(L/W/H) mm	800x800x2200
[2] Inverter	(L/W/H) mm	673x626x621
Weight Battery Rack	kg	1250
Weight ConnectionBox	kg	25
Weight Inverter	kg	69
Protection rating Battery Rack	IP	20
Protection rating Inverter	IP	65
Max. permissible installation height	m	2000
Operating temperature range	°C	10-40
Product warranty	Years	5
Performance warranty	Years	10



Safety devices

Permanent monitoring of the battery cells	√

www.pramac.com

Certificates / Approvals

Battery Rack
Modul:
UN38.3 / UL 9540A
Rack:
CE / IEC 62619 / IEC 63056 / UL 1973 / VDE 2510 50 / EN 61000-6-2 / EN 61000-6-4



Battery Inverter
EU- Directives:
2014/30/EU / 2014/35/EU / 2011/65/EU / 2015/863/EU
Safety Battery Inverter:
IEC 62109-1 / IEC 62109-2 / IEC 62116 / IEC 61727 / IEC 62477-1 / IEC 61439-1 / IEC 61439-2
EMC:
EN 61000-6-2 / EN 61000-6-4 / EN 61000-3-12 / EN 61000-3-11
Grid codes: DIN VDE V 0126-1-1 / VDE AR-N 4105:2018 / VDE AR-N 4110:2023 / C10/C11 / G99/1-9 / TOR Stromerzeugungsanlagen Typ A/B / CEI 0-16, CEI 0-21 / EN 50549-1/-2 / AS4777.2 / NTS 631, UNE 27002
For other grid codes please contact your local sales representative

Optional features	
Optional Router	•
Optional Energy Meter Ethernet	•
Optional Energy Meter RS485	•
CombinerRack Single / Dual	•
Extension Kit 109	•
Upgrade Kit CombinerRack	•



www.pramac.com

The information is aligned with the Data file at the time of download.
Printed on 23/03/2026 (ID 191334)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc.| All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice