E4500 230V 50HZ

ENERGY AT FAIR PRICE



Simple professional generator. Pramac has designed this generator to ensure a high performance level at attractive price. Powerful and strong generator; easy to maintain, it will be soon essential to all your activities.

Main Features		
Frequency	Hz	50
Voltage	V	230
Power factor	cos ϕ	0.9
Phase		1

Power Rating		
Emergency Standby Power ESP	kVA	3.9
Emergency Standby Power ESP	kW	3.5
Continuous power COP	kVA	3.3
Continuous power COP	kW	3.0

Ratings definition (ISO-8528)
ESP - Emergency Standby Power:
It is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.
COP - Continuos Power:
It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedure being carried out as prescribed by the manufacturers.

www.pramac.com

Engine specifications		
Engine Brand		Yanmar
Model		L70N
Engine cooling system		Air
Displacement	cm³	320
Aspiration		Natural
Operating Speed-Nominal	rpm	3000
Speed governor		Mechanical
Fuel		Diesel
Oil capacity	l	1.1
Starting system		Electric



Alternator Specifications		
Type		Brushless
Class		H
IP protection		23
Poles		2
Frequency	Hz	50
Voltage tolerance	%	+5, - 10 (cosϕ1)
Voltage regulation system		Capacitor

Dimensional data		
Length	(L) mm	760
Width	(W) mm	540
Height	(H) mm	560
Dry weight	kg	56
Fuel tank capacity	l	3.5

Autonomy		
Fuel consumption at 75% of Load	l/h	1.16
Fuel consumption at 100% of Load	l/h	1.24
Running time at 75% of load	h	3.02
Running time at 100% of load	h	2.82

www.pramac.com

GENSET CONTROL



COMMANDS:
- Start selector switch with key: OFF - ON - START
- Fuel Cock

PROTECTIONS STANDARD:
- Thermal protection

SOCKET TYPE

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 16A IP44	1

SUPPLEMENTS CONTROL (Available when ordered)

Electrical box DPP + HM



Extra Protection with:
- Differential protection 30mA
- Circuit breaker
- Hourmeter

www.pramac.com

ACCESSORIES

TRANSPORTATION KIT

- With fix handles



- With folding handles



www.pramac.com

The information is aligned with the Data file at the time of download. Printed on 24/03/2023 (ID 4555)

©2023 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice